



IoT-Based Smart Home Automation System Using ESP32 and Blynk Cloud Platform

¹Harsh Kumar, ²Anusha Kurmi, ³Geetika Vishwakarma, ⁴Divyansh Nigam, ⁵Dr. Uma Shankar Kurmi

^{1/2/3/4} Student, ⁵Guide

Department of ECE, LNCT, Bhopal, India

ABSTRACT

The Internet of Things (IoT) has emerged as a transformative technology for modern smart environments. This research paper presents the design and implementation of an IoT-based home automation system using ESP32 and Arduino microcontrollers integrated with voltage and current sensors. The proposed system enables users to remotely control LED loads and regulate fan speed through the Blynk cloud platform using Wi-Fi communication. Real-time monitoring of electrical parameters such as voltage, current, and power consumption is achieved through sensor integration and cloud synchronization. Experimental results demonstrate stable communication, accurate sensing, low latency, and reliable operation of connected appliances. The developed system is economical, scalable, energy-efficient, and suitable for modern smart home applications.

Keywords: IoT, ESP32, Home Automation, Blynk, Smart Home, Wi-Fi, Voltage Sensor, Current Sensor.

1.INTRODUCTION

Smart home automation systems are increasingly being adopted in residential and commercial environments because they provide intelligent control, reduced energy wastage, and enhanced user convenience. IoT technology enables seamless interaction between users and electronic appliances through cloud platforms and mobile applications. In recent years, the availability of low-cost microcontrollers and cloud-based services has accelerated the development of affordable automation systems for educational and industrial applications.

The use of ESP32 microcontrollers in IoT applications has gained popularity because of their powerful processing capability, integrated wireless communication, and support for multiple sensors and actuators. By combining ESP32 with the Blynk platform, users can monitor and control appliances in real time from any location with internet connectivity. Such systems contribute significantly to energy conservation and efficient power utilization.

The Internet of Things (IoT) represents one of the most significant technological advancements in the field of embedded systems and wireless communication. IoT enables physical devices to communicate through internet connectivity and exchange information without human intervention. Smart home automation has become one of the most popular applications of IoT because it allows users to remotely control household appliances, improve energy efficiency, and enhance safety and comfort. With the growing demand for intelligent residential systems, researchers and industries are focusing on developing cost-effective and scalable home automation solutions.



Traditional electrical systems mainly depend on manual switching mechanisms and do not provide real-time monitoring or remote accessibility. Such systems often lead to unnecessary energy consumption and lack proper energy management capabilities. Modern smart homes require systems that can monitor electrical parameters continuously while also allowing users to operate appliances from remote locations through smartphones or cloud platforms.

The proposed IoT-based smart home automation system utilizes ESP32 and Arduino microcontrollers along with voltage and current sensing modules to create an intelligent and efficient home environment. The ESP32 controller provides built-in Wi-Fi connectivity, making it suitable for cloud-based IoT applications. The Blynk cloud platform enables real-time communication between the hardware system and the user's smartphone application. Through this integration, users can remotely control LED loads, regulate fan speed, and monitor electrical parameters such as voltage, current, and power consumption. The proposed system is designed to be economical, scalable, user-friendly, and suitable for future smart city applications.

Several modern studies have emphasized the importance of integrating cloud computing with IoT systems to improve scalability and remote accessibility. Researchers have also explored mobile-based monitoring systems that provide graphical visualization of energy consumption and appliance status. However, many existing systems focus only on basic control functionality and do not provide complete electrical parameter analysis.

Some researchers have utilized GSM-based communication for appliance control, but such systems are comparatively slower and less efficient than Wi-Fi-based IoT systems. Bluetooth-based automation systems provide limited operational range and are not suitable for remote internet-based applications. Therefore, Wi-Fi-enabled controllers such as ESP32 offer a better alternative because they support fast communication and cloud connectivity with minimal hardware requirements.

2. LITERATURE REVIEW

Researchers across the world have developed various IoT-enabled home automation systems using wireless communication technologies such as Wi-Fi, Bluetooth, ZigBee, and GSM. Early home automation systems mainly focused on simple ON/OFF control of appliances using GSM modules and SMS-based communication. Although these systems provided remote accessibility, they suffered from limitations such as slow response time, high operational cost, and lack of real-time monitoring.

Recent advancements in IoT technology and cloud computing have significantly improved smart home systems. ESP32-based automation systems have become popular due to their low cost, compact size, low power consumption, and integrated Wi-Fi and Bluetooth functionalities. Several researchers have integrated cloud platforms such as Blynk, ThingSpeak, and Firebase for remote appliance control and sensor data visualization. These platforms provide user-friendly dashboards and enable real-time data synchronization.

Existing systems mainly concentrate on appliance switching but often lack advanced functionalities such as electrical parameter monitoring, power analysis, and fan speed regulation. Some studies include energy monitoring systems but require expensive hardware and complex implementation. The proposed research addresses these limitations by



integrating appliance control, real-time energy monitoring, and PWM-based fan speed control into a single compact and economical system.

Recent studies using ESP32 microcontrollers have improved wireless communication reliability and reduced implementation cost. Cloud platforms such as Blynk have simplified IoT deployment by providing efficient dashboards for remote monitoring and control.

3. PROBLEM FORMULATION

Conventional electrical systems in residential buildings are inefficient because they require manual operation and provide no intelligent monitoring capabilities. In many households, appliances remain switched ON unnecessarily, resulting in increased energy consumption and higher electricity costs. Furthermore, users cannot monitor electrical parameters such as voltage fluctuations, current consumption, or total power utilization in real time.

Another major challenge in traditional systems is the absence of remote accessibility. Users cannot operate appliances when they are away from home, which reduces convenience and flexibility. Existing automation systems available in the market are often expensive and difficult to install, making them unsuitable for widespread adoption in developing regions.

The objective of the proposed research is to develop a low-cost and reliable IoT-based smart home automation system capable of remote appliance control, real-time monitoring of voltage and current, fan speed regulation using PWM techniques, and stable cloud communication through Wi-Fi technology. The proposed system aims to overcome the limitations of traditional systems by providing a scalable, economical, and intelligent automation solution.

The hardware architecture of the proposed system is designed to ensure efficient communication and reliable operation. The ESP32 continuously exchanges data with the Blynk cloud server, allowing users to monitor and control appliances using a smartphone interface. The relay modules act as electrically operated switches capable of controlling high-voltage loads safely through low-voltage control signals.

Voltage and current monitoring play an important role in analysing power consumption and improving energy efficiency. The current sensor measures the flow of electrical current in connected loads, while the voltage sensor monitors supply voltage conditions. The collected sensor data helps users understand appliance behaviour and detect abnormal operating conditions.

4. PROPOSED METHODOLOGY

The proposed methodology is based on the integration of hardware and software modules for intelligent home automation. The ESP32 microcontroller acts as the central processing unit because of its built-in Wi-Fi capability and efficient performance in IoT applications. Arduino is used for additional control tasks such as fan speed regulation through Pulse Width Modulation (PWM).

The system consists of relay modules, voltage sensors, current sensors, fan control circuitry, and the Blynk cloud platform. Relay modules are connected to household appliances such as LED loads to perform switching operations. Voltage and current sensors continuously measure electrical parameters and transmit the data to the ESP32 controller. The collected data is processed and uploaded to the Blynk cloud dashboard through Wi-Fi communication.



The Blynk application provides an interactive graphical interface where users can monitor sensor values and remotely operate appliances. The fan speed is controlled using PWM signals generated by the Arduino microcontroller. Multiple speed levels are implemented to ensure smooth operation and energy optimization.

The proposed architecture ensures reliable communication, low latency, and efficient synchronization between the hardware system and cloud platform. The modular design also allows future expansion of the system by integrating additional sensors, security modules, and artificial intelligence-based automation features.

The system also enables remote appliance control through a smartphone application.

5. SYSTEM ALGORITHM

The system initializes all hardware modules and establishes Wi-Fi communication. After successful Blynk cloud authentication, user commands are received from the mobile application. Relay modules switch connected loads according to the received commands. Voltage and current sensors continuously measure electrical parameters, and the measured values are uploaded to the cloud dashboard in real time.

The developed prototype was tested under different operating conditions to evaluate system performance and reliability. Experimental analysis showed that the Wi-Fi communication remained stable during continuous operation, and cloud synchronization was successfully maintained without significant interruptions. The relay switching mechanism operated accurately according to user commands received from the Blynk application.

Sensor calibration was performed to improve the accuracy of voltage and current measurements. The obtained results indicated that the system could effectively monitor electrical parameters with acceptable precision for smart home applications. Fan speed regulation through PWM provided smooth operation and minimized sudden changes in motor speed, thereby improving user comfort and reducing power consumption.

6. IMPLEMENTATION AND RESULTS

The hardware implementation of the proposed system was carried out using ESP32, Arduino UNO, relay modules, ACS712 current sensor, voltage sensor module, and DC fan control circuitry. The ESP32 controller was programmed using the Arduino IDE environment and configured for Wi-Fi communication with the Blynk cloud platform.

Experimental testing demonstrated stable communication between the hardware modules and the cloud dashboard. LED loads were successfully controlled remotely through the smartphone application with minimal response delay. The voltage and current sensors provided accurate measurements under normal operating conditions, and the measured data was continuously displayed on the Blynk interface.

Fan speed control was implemented using PWM techniques, allowing smooth variation across multiple speed levels. The system achieved reliable synchronization between hardware and cloud communication with low latency. Power consumption calculations were performed using real-time voltage and current values obtained from the sensors.

The testing results confirmed that the proposed system operates efficiently and reliably for smart home applications. The system also demonstrated scalability and can be expanded to include additional appliances and monitoring features.



Testing results confirmed successful remote operation of LED loads and real-time monitoring of voltage and current values through the Blynk application. The system achieved low-latency cloud synchronization and reliable performance under normal operating conditions.

The research work demonstrates that IoT technology can significantly improve the efficiency and intelligence of home electrical systems. The proposed automation system combines wireless communication, cloud computing, and sensor integration to provide a reliable and practical solution for modern smart homes. The developed system can be implemented in residential buildings, offices, laboratories, and educational institutions for efficient energy management.

The future scope of this project includes integration with renewable energy systems, smart security modules, and advanced data analytics for predictive maintenance. The incorporation of artificial intelligence and machine learning techniques can further enhance automation capabilities by enabling automatic decision-making based on user behaviour and environmental conditions.

7. CONCLUSION

The proposed IoT-based smart home automation system successfully demonstrated intelligent appliance control, cloud-based monitoring, and energy management using ESP32 and Blynk technology. The integration of voltage and current sensors enabled real-time monitoring of electrical parameters, while PWM-based fan speed regulation improved energy efficiency and user convenience.

The developed system offers several advantages including low implementation cost, wireless operation, scalability, user-friendly interface, and reliable cloud synchronization. The experimental results validated the effectiveness of the proposed design under practical operating conditions. The system is suitable for modern smart homes, educational projects, and industrial prototype development.

Future enhancements may include integration of voice assistants such as Google Assistant and Amazon Alexa, machine learning algorithms for predictive energy analysis, automated scheduling systems, and advanced safety mechanisms including fire detection and overload protection. The implementation of artificial intelligence-based decision-making can further improve the efficiency and intelligence of the smart home environment.

Power Calculation

$$P = V \times I$$

Table 1. Performance results

Feature Tested	Expected Output	Achieved Result
Wi-Fi Connection	Stable Link	Connected Successfully
LED Control	Remote ON/OFF	Fully Functional
Fan Speed Regulation	Variable Speed	Smooth 0–5 Levels
Voltage Monitoring	Real-Time Values	Accurate Readings
Current Monitoring	Live Monitoring	Successfully Measured

8. FUTURE SCOPE

The future development of IoT-based smart home automation systems will focus on improving intelligence, security, and energy optimization. Advanced cloud computing



technologies and artificial intelligence algorithms can be integrated into the system to enable predictive analysis and automated decision-making. Machine learning techniques can analyse user behaviour patterns and automatically control appliances to maximize comfort and minimize energy consumption. Voice-controlled assistants such as Google Assistant and Amazon Alexa can also be integrated with the proposed system to provide hands-free operation. Additional safety features such as smoke detection, gas leakage monitoring, fire alarms, and intrusion detection systems can further improve the reliability and security of smart homes. Renewable energy integration and smart grid compatibility are also promising areas for future research and development.

REFERENCES

1. Blynk IoT Platform Documentation, Available: <https://docs.blynk.io>
2. Espressif Systems, “ESP32 Technical Reference Manual,” 2022.
3. M. Gupta and K. Sharma, “Design and Implementation of IoT-Based Energy Monitoring System Using Sensors,” IEEE Conference on Smart Technologies, pp. 215–220, 2021.
4. N. Priya and R. Kumar, “IoT-Based Smart Home Automation System Using ESP32 Microcontroller,” IJERT, vol. 9, no. 6, pp. 120–125, 2023.
5. P. Singh and A. Verma, “Remote Home Appliance Control Using Blynk Cloud Platform,” IJARCS, vol. 11, no. 4, pp. 45–50, 2022.
6. S. Patel and V. Yadav, “Wi-Fi Enabled Home Automation Using ESP32 and Arduino,” International Journal of Embedded Systems, vol. 5, no. 2, pp. 89–94, 2022.